

Bread maker improves safety through changes to filtration process

Location:

Toronto, Ontario, Canada

Segment:

Food and beverage

Challenge:

The potential hazards to operators when manually changing filter media while working with high water temperatures

Solution:

Eaton's mechanically cleaned DCF-800 filter

Results:

A safer work environment plus additional financial and environmental gains recognized by replacing filter with automatic cleaning Eaton's mechanically cleaned filters are believed to be one of the most efficient mechanically cleaned filters on the market

Background

Based on the appearance a bagel, a bakery item that is growing in popularity around the world, it's hard to imagine that processing these delicious treats may pose an occasional hazard.

According to officials at a Canadian bread manufacturing company based in Ontario, it's true.

Highly pressurized hot water is used extensively in the bagel making process and requires boiling to offset potential quality problems. The process also requires a filtration system to clean raisins, sesame seeds, bits of dough, cornmeal, and other materials out of the hot water. And that's where the danger can occur.

The company was using a different filtration system for several years and was concerned about employee safety because of the hazards associated with manually changing filter media while working with the high water temperatures.

Challenge

Plans were in place to install a new bagel boiler in its Canadian plant and it required a filtering system to clean the recycled boiler water of raisins, sesame seeds, bits of dough and cornmeal. Cornmeal can create water quality problems if the temperature falls below a certain level, requiring an expensive and time-consuming water change. It is critical that the water in a bagel boiler remain at a high temperature, even as it is filtered and recycled.

With the safety of its employees a top priority, the maintenance supervisor at the company's plant wanted a filtration system that required less operator intervention. High water temperatures used in the process can be a serious hazard to an operator changing filter media, especially when pressed for time during the shutdown process, when an operator may open up the filtration system while it is still pressurized.



According to the U.S. Center for Disease Control and Prevention (CDC) website, workers exposed to conditions of extreme heat in the workplace may be at risk of developing heat stress. Continued exposure to high levels of heat can result in occupational health issues and injuries such as burns from hot surfaces or steam, heat stroke, heat exhaustion or heat rashes. The CDC site goes on to say that working in conditions with extreme heat, like those encountered during the bagel making process, can also increase the hazards workers may experience like fogged-up safety glasses and dizziness.

"Safety in the workplace is the joint responsibility of the entire workforce of an organization," comments said Mary Jo Surges, vice president and general manager, Eaton's Filtration Division. "At Eaton, we are committed to improving employee safety, reducing energy and water use, and waste generation. We work with organizations around the world every day to help attain these goals."

Solution

Decision makers at the plant wanted a filter they could count on, without the hazards that can be associated with filter media maintenance. Working with Eaton, the plant manager and maintenance supervisor determined that the Eaton DCF mechanically cleaned filter was the permanent solution to meet their business objectives. The plant installed two Eaton DCF-800 filters on the boiler water recycle line at their facility. DCF filters successfully removed the raisins sesame seeds bits of dough, and cornmeal that would adversely affect the final product. Uninterrupted filtering by the DCF also ensured consistently high water temperatures required to maintain boiler water quality.

The DCF filter performs a selfcleaning action by mechanically scraping collected debris from the filter screen with a disc that travels up and down the screen. parallel to the liquid flow. The collection chamber at the bottom of the filter automatically purges collected debris without halting production, in a process that takes less than seventenths of a second. Because the DCF filter continuously cleans the screen without interrupting production, it maintains a consistently high flow rate and provides the highest quality filtering. In addition, this filter collects and discharges only the contaminants.

Results

The company has eliminated the risk of operator injury related to changing filter media because cleaning of the DCF filter is automatic.

The facility's supervisors were also impressed with the unsurpassed filtering of its bagel boiler water, the ability to a maintain high water temperature, and avoid water quality problems. Meanwhile, the plant is realizing financial and environmental gains by eliminating media, reducing worker exposure, and reducing labor and disposal costs.

The company was so happy with the performance of the DCF filters at its initial installation, they also installed DCF filters on its bagel boiler systems at a second location.



Eaton's mechanically cleaned filters are believed to be one of the most efficient mechanically cleaned filters on the market.

North America 44 Apple Street Tinton Falls, NJ 07724 Toll Free: 800 656-3344 (North America only)

Tel: +1 732 212-4700

Tel: +49 2486 809-0

Europe/Africa/Middle East Auf der Heide 2 53947 Nettersheim, Germany

Friedensstraße 41 68804 Altlußheim, Germany Tel: +49 6205 2094-0

An den Nahewiesen 24 55450 Langenlonsheim, Germany Tel: +49 6704 204-0

No. 3. Lane 280. Linhong Road Changning District, 200335 Shanghai, P.R. China Tel: +86 21 5200-0099

Singapore

4 Loyang Lane #04-01/02 Singapore 508914 Tel: +65 6825-1668

Av. Julia Gaioli. 474 – Bonsucesso 07251-500 - Guarulhos, Brazil Tel: +55 11 2465-8822

For more information, please email us at filtration@eaton.com or visit www.eaton.com/filtration

© 2016 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommen dations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.

